§ 307.5

would seriously handicap the Department in carrying out its function. These provisions are applicable to all official establishments except in certain cases as provided in §318.4(h) of this subchapter.

- (d)(1) Each official establishment shall submit a work schedule to the area supervisor for approval. In consideration of whether the approval of an establishment work schedule shall be given, the area supervisor shall take into account the efficient and effective use of inspection personnel. The work schedule must specify daily clock hours of operation and lunch periods for all departments of the establishment requiring inspection.
- (2) Establishments shall maintain consistent work schedules. Any request by an establishment for a change in its work schedule involving an addition or elimination of shifts shall be submitted to the area supervisor at least 2 weeks in advance of the proposed change. Frequent requests for change shall not be approved: *Provided*, however, minor deviations from a daily operating schedule may be approved by the inspector in charge, if such request is received on the day preceding the day of change.
- (3) Request for inspection service outside an approved work schedule shall be made as early in the day as possible for overtime work to be performed within that same workday; or made prior to the end of the day's operation when such a request will result in overtime service at the start of the following day: *Provided*, That an inspector may be recalled to his assignment after completion of his daily tour of duty under the provisions of § 307.6(b).

[40 FR 45799, Oct. 3, 1975, as amended at 40 FR 50719, Oct. 31, 1975; 41 FR 15401, Apr. 13, 1976; 48 FR 6893, Feb. 16, 1983; 51 FR 32304, Sept. 11, 1986]

## § 307.5 Overtime and holiday inspection service.

(a) The management of an official establishment, an importer, or an exporter shall reimburse the Program, at the rate specified in §391.3, for the cost of the inspection service furnished on any holiday as specified in paragraph (b) of this section; or for more than 8 hours on any day, or more than 40

hours in any administrative workweek Sunday through Saturday.

(b) Holidays for Federal employees shall be New Year's Day, January 1; Birthday of Martin Luther King, Jr., the third Monday in January; Washington's Birthday, the third Monday in February; Memorial Day, the last Monday in May; Independence Day, July 4; Labor Day, the first Monday in September; Columbus Day, the second Monday in October; Veterans' Day, November 11; Thanksgiving Day, the fourth Thursday in November; Christmas Day, December 25. When any of the above-listed holidays falls outside the basic workweek, the nearest workday within that week shall become a holiday.

[40 FR 45800, Oct. 3, 1975, as amended at 43 FR 51754, Nov. 7, 1978; 50 FR 724, Jan. 7, 1985; 50 FR 51513, Dec. 18, 1985; 52 FR 4, Jan. 2, 1987; 33 FR 13397, Apr. 22, 1988; 54 FR 6389, Feb. 10, 1989]

## § 307.6 Basis of billing for overtime and holiday services.

- (a) Each recipient of overtime or holiday inspection service, or both, shall be billed as provided for in §307.5(a) and at the rates specified in §391.3, in increments of quarter hours. For billing purposes, 8 or more minutes shall be considered a full quarter hour. Billing will be for each quarter hour of service rendered by each Program employee.
- (b) Official establishments, importers, or exporters requesting and receiving the services of a Program employee after he has completed his day's assignment and left the premises, or called back to duty during any overtime or holiday period, shall be billed for a minimum of 2 hours overtime or holiday inspection service at the established rate.
- (c) Bills are payable upon receipt and become delinquent 30 days from the date of the bill. Overtime or holiday inspection will not be performed for anyone having a delinquent account.

[40 FR 45800, Oct. 3, 1975, as amended at 54 FR 6389, Feb. 10, 1989]

## § 307.7 Safety requirements for electrical stimulating (EST) equipment.

(a) General. Electrical stimulating (EST) equipment is equipment that provides electric shock treatment to

carcasses for the purpose of accelerating rigor mortis of facilitating blood removal. These provisions do not apply to electrical equipment used to stun and/or slaughter animals or to facilitate hide removal. Electrical stimulating equipment consists of two separate pieces—the control system and the applicator. The EST control system contains the circuitry to generate pulsed DC or AC voltage for stimulation and is separate from the equipment used to apply the voltage to the carcass. The voltage is applied by inserting a probe that penetrates the carcass or is inserted in the rectum, placing a clamp in the nose, a carcass rubbar, a conveyor with energized surfaces traveling with the carcass, or any other acceptable method.

- (b) Safety requirements—(1) Circuits, grounding. Either a bonded grounding conductor shall lead from each section of the carcass rail within the stimulating enclosure to the service ground or the secondary voltage (stimulating circuit) shall be insulated from the service ground. If the stimulating section of the carcass rail and carcass drive mechanisms are insulated from the service ground then the stimulating rail or the return path shall be electrically bonded to the transformer secondary to isolate the stimulation voltage.
- (2) Enclosure. Electrical stimulation shall occur in an area that will prevent persons from contacting an energized surface. If the area is surrounded by physical barriers, the enclosure shall be either electrically grounded or it shall be made of materials that do not conduct electricity. The interior of the stimulating area shall be visible from the start switch so the operator can be assured that there is no person, equipment or material present that should not be there prior to starting the stimulating sequence. If light or sound beam sensors form the enclosure, the stimulating equipment shall be automatically shut off when the sensor signals are broken.
- (3) Mandatory Warning Devices and Signals. The following warning devices or signals shall be installed at each opening to the stimulating area through which a person would normally enter:

- (i) A red light that flashes distinctly during the operating cycle of the stimulating equipment.
- (ii) An ANSI Z53.1-Color Code sign reading (a) "Danger Electrical Hazard" for stimulating voltage below 50 or (b) "Danger High Voltage" for stimulating voltage above 50.
  - (iii) An emergency stop button.
- (4) Optional Warning Device—Horn or Bell. If a warning horn or bell is installed, the signal shall be audible above background noises in the vicinity, and it shall sound for at least 1 second before each manual stimulation or before the carcass chain is started in an automatic system.
  - (c) Operation-
- (1) *Training.* Only persons who have received safety instruction by the equipment manufacturer or designee may operate electrical stimulating equipment.
- (2) Cleaning and Maintenance. To prevent an electrical shock to personnel, the electricity supplied to the stimulating surfaces shall be locked-off when cleaning, mechanical inspection, maintenance or testing are performed.
- (3) Water. To prevent an electrical shock, personnel shall not spray streams of water on energized carcasses or on energized stimulating surfaces.
- (d) Special provisions for manually operated equipment.
- (1) Stimulating probes or clamps shall be stored in a sanitary container which is insulated with a material approved by the Administrator.<sup>1</sup>
- (2) The electric wires attached to a clamp or probe shall not allow for contact between the probe or clamp and an electrical ground and shall not extend outside the enclosure.

[53 FR 46432, Nov. 17, 1988, as amended at 64 FR 56415, Oct. 20, 1999]

## PART 308 [RESERVED]

<sup>&</sup>lt;sup>1</sup>A list of approved insulation materials is available upon request from the Facilities, Equipment and Sanitation Division, Technical Services, Food Safety and Inspection Service, U.S. Department of Agriculture, Washington, DC 20250.